




SCREWS- PHILIPS CSK HEAD SCREW FULL THREADED



STAINLESS STEEL

DIN 965



**DIN 965
PHILLIPS CSK HEAD SCREW FULL THREADED**

MVD PART NO DESIGNATION

MV	PCSK	MX	LX	S / SS	XX
MV	965	MX	LX	S / SS	XX
	↓	↓	↓	↓	↓
	DIN NO	THREAD	LENGTH	Material Code	Plating Code

Thread (D)		M2.5	M3	(M3.5)	M4	M5	M6	M8	M10	
P		0.45	0.5	0.6	0.7	0.8	1	1.25	1.5	
DK	nominal	5	5.6	6.5	7.5	9.2	11	14.5	18	
	max.	4.4	5.3	6.14	7.14	8.84	10.57	14.07	17.57	
K	max.	1.5	1.65	1.93	2.2	2.5	3	4	5	
A	max.	0.9	1	1.2	1.4	1.6	2	2.5	3	
B	min.	18	19	20	22	25	28	34	40	
r	max.	0.70	0.8	0.95	1	1.3	1.6	2	2.5	
X	max.	1.1	1.25	1.5	1.75	2	2.5	3.2	3.8	
Cross recess		no.	1.00	1	2	2	3	4	4	
Type H	M	approx.	2.7	2.9	3.9	4.4	4.6	6.6	8.7	9.6
	penetration depth	min.	1.3	1.5	1.4	1.9	2.1	2.8	3.9	4.8
		max.	1.6	1.8	1.9	2.4	2.6	3.3	4.4	5.3
Length		As Per Requirement								

Fastening Everything

SPECIFICATIONS & DETAILS			
MVD PART CODE	MVPCSKMXXXX	MVD DESCRIPTION	PHILLIPS CSK SCREW FULL THREAD SS304 MXX
DRAWN BY	ABHISHEK	APPROVED BY	MAGESH
DRAWING REV. NO	00	MATERIAL	STAINLESS STEEL
DATE		FINISH	SELF FINISH
ALL DIMENSIONS ARE IN MM, UNLESS SPECIFIED			

